

**AXESS TMC**

ZucchettiGroup



**XCELLENCE IN SOLUTIONS**  
**XCELLENCE IN COMPONENTS**

## 962 SuperTrax

### Design and high Technology

*SuperTrax* is the latest AXESS TMC terminal featuring the most advanced data collection technology in a modern and stylish case.

All this at an astonishing competitive price.



*SuperTrax* means latest technology and modern design, at a very competitive price.

*SuperTrax* redefines the concept of data collection terminal and facilitates the design and deployment of complex applications with ease. Communication with servers and integration with third party software can also be performed effortlessly.

### All data at your fingertips

The simple but modern and stylish design, with its friendly and flexible interface, makes *SuperTrax* the most advanced Time & Attendance terminal on the market at a very competitive price. The built-in standard Time & Attendance application can be easily integrated with other applications, including HR management.

Workflow procedures for processing holiday, authorizations, travel expenses or general inquires regarding balances, among others, can be easily developed in standard languages, such as ".NET" or "HTML".

**AXESS TMC**

AXESS TMC Srl  
Via della Filanda 22 • 40133 Bologna  
Tel. 051 3519311 • Fax 051 3519399  
Via Turati, 111 • 20023 Cerro Maggiore (MI)  
Tel. 0331423211 • Fax 0331423299  
Email: [contact@axesstmc.com](mailto:contact@axesstmc.com)  
[www.axesstmc.com](http://www.axesstmc.com)

**XCELLENCE IN SOLUTIONS** **XCELLENCE IN COMPONENTS**



## Options

Slot readers (magnetic or barcode) are available options that work together with the internal RFID reader where double ID technologies are required.

Biometric modules with optical or capacitive sensors deliver the same unrivaled technology as the terminal itself and can be used in 1:N or 1:1 modes, with up to 9500 templates.



## Technical specifications

<b>Human interface</b>	Display TFT 7" 16:9 800x480, LED backlit, touch screen 1 key with blue led Vertical or horizontal mounting
<b>Ports</b>	2 USB 1.1 host ports 1 x Ethernet 10/100 Power Over Ethernet A&B compliant 1 x Serial RS232 optocoupled 1 x RS485 (NET92 master protocol can be enabled)
<b>Readers</b>	Internal RFID reader in any of the technologies supported by AXESS TMC: <ul style="list-style-type: none"> <li>• 125KHz EM4102 compatibles (dual - head)</li> <li>• 125KHz HID</li> <li>• 13.56MHz multi-standard R&amp;W ISO14443/15693 (with Mifare)</li> <li>• 13.56MHz Legic advant muti-standard hi-security R&amp;W ISO14443/15693</li> </ul> External optional swipe reader: Magnetic or barcode External optional fingerprint reader with capacitive or optical sensor (1:N or 1:1)
<b>Physical Input outputs</b>	2 x Relays 1A 30V configurable: Normally Open or Normally Closed 2 x Digital optocoupled inputs for dry contacts
<b>Electrical</b>	Backup battery: 40 minutes continued operation in case of power failure Power Supply: 12....48 VDC 5...7W (up to 10W during fast battery charge)
<b>Options</b>	WiFi 802.11 b/g (USB) GSM / GPRS modem (USB) Memory Key (USB) PSTN 56K analog modem
<b>Fingerprint</b>	Optional external biometric reader with optical or capacitive sensor - 9500 templates 1:N (AXESS TMC recommends up to 1000 users in identification mode) 1:1 with templates on terminal's memory or on RFID card
<b>Audio</b>	1W Mono Speaker with wav and mp3 playback capabilities Microphone for recording functions
<b>Software services</b>	Compact .NET framework 2.0 FTP server, Web server IE6 compliant jscript and vbscript Telnet - Remote desktop client Internet browser (also integrated in internal T&A application)
<b>Hardware features</b>	64 Mbyte RAM and 64 MBflash (30 MB available as internal flash disk expandable to GBs with USB Keyfob)
<b>Physical</b>	<b>Casing:</b> ABS V0, auto-extinguish <b>Dimensions:</b> 132x232x52 mm (HxLxW) <b>Weight:</b> 1 Kg